

PRODUCT NAME

MATERIALS

Primary Yarn Polymer	Polyethylene
Yarn Cross Section	Slit-Film
Standard Color	Meadow Green
UV Stabilized	Yes
Fabric Construction	Tufted
Secondary Yarn Polymer	Texture Nylon
Secondary Yarn Color	Green
Primary Backing	13 Pic Woven (2)
Coating Type	5mm Polyurethane Foam
Polyethylene Yarn	8,000/1
Texturized Thatch	4,200/8
Sustainability	100% Recyclable
<i>Warranty Period</i>	8 years

Finish Fabric	English		ASTM
	Valu	Units	Metho
<i>Nominal Specification</i>			
Pile Height(Nominal)	7/8	inche	D-582
Face Weight	58	oz/	D-584
Total Fabric Weight		oz/	D-584
Primary Backing Weight	7	oz/	D-584
Secondary Coating	20	oz/	D-584
Tuft Bind	>8	lbs.	D-133
Grab Tear	>200	lbs.	D-503
Lead Content	<50	ppm	F-276
Total Yarn Linear Density	15,84	Denie	D-157
Elongation to Break	>60	%	D-225
Yarn Breaking Strength	>19	lbs.	D-225
Yarn Melting Point	248	F°	D-713
Stitch Rate	6.7	in	D-579
Machine Gauge	3/16	inche	D-579
Flammability	Pass		D-285
Water Permeability	>30	in/hr	DIN
Fabric Width	15	ft	

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are ± 5%.

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are $\pm 5\%$.