

PRODUCT NAME					
		S69A			
MATERIALS					
Primary Yarn Polymer					Polyethylene
Yarn Cross Section					“S” Shape Monofilament
Standard Color					Field Green/Apple Green
UV Stabilized					Yes
Fabric Construction					Tufted
Secondary Yarn Polymer Thatch					Texture Polyethylene
Secondary Yarn Color					Field Green/Tan
Primary Backing					13 Pic Woven (2)
Coating Type					Polyurethane
Polyethylene Yarn Denier / Ends					12,000/6
Texturized Thatch Denier /Ends					5,040/8
Sustainability					100% Recyclable
Warranty Period					10 years
Finish Fabric	English System		ASTM Standards		
<i>Nominal Specification</i>	<i>Value</i>	<i>Units</i>	<i>Method</i>		
Pile Height(Nominal)	1 7/8	inches	D-5823		
Face Weight	69	oz/yd ²	D-5848		
Total Fabric Weight	96 107	oz/yd ²	D-5848		
Primary Backing Weight	7	oz/yd ²	D-5848		
Secondary Coating Weight	20	oz/yd ²	D-5848		
Tuft Bind	>8	lbs.	D-1335		
Grab Tear Strength(Average)	>200	lbs.	D-5034		
Lead Content	<50	ppm	F-2765		
Total Yarn Linear Density	17,040	Denier	D-1577		
Elongation to Break	>60	%	D-2256		
Yarn Breaking Strength	>19	lbs.	D-2256		
Yarn Melting Point	248	F°	D-7138		
Stitch Rate	3.7	in	D-5793		
Machine Gauge	3/8	inches	D-5793		
Flammability	Pass		D-2859		
Water Permeability	>30	in/hr	DIN 18-035		
Fabric Width	15	ft	None		

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are $\pm 5\%$.