

## PRODUCT NAME

**LS**

### MATERIALS

Primary Yarn Polymer	Polyethylene
Yarn Cross Section	Diamond Monofilament
Standard Color	Field Green/Olive Green
UV Stabilized	Yes
Fabric Construction	Tufted
Secondary Yarn Polymer	Texture Polyethylene
Secondary Yarn Color	Green/Tan
Primary Backing	13 Pic Woven (2)
Coating Type	Polyurethane
Polyethylene Yarn	10,800/6
Texturized Thatch	4,200/8
Sustainability	100% Recyclable
<i>Warranty Period</i>	<b>8 years</b>

Finish Fabric	English		ASTM
<i>Nominal Specification</i>	<i>Valu</i>	<i>Units</i>	<i>Metho</i>
Pile Height(Nominal)	1 5/8	inche	D-582
Face Weight	80	oz/	D-584
Total Fabric Weight		oz/	D-584
Primary Backing Weight	7	oz/	D-584
Secondary Coating	20	oz/	D-584
Tuft Bind	>8	lbs.	D-133
Grab Tear	>200	lbs.	D-503
Lead Content	<50	ppm	F-276
Total Yarn Linear Density	15,00	Denie	D-157
Elongation to Break	>60	%	D-225
Yarn Breaking Strength	>19	lbs.	D-225
Yarn Melting Point	248	F°	D-713
Stitch Rate	4	in	D-579
Machine Gauge	3/8	inche	D-579
Flammability	Pass		D-285
Water Permeability	>30	in/hr	DIN
Fabric Width	15	ft	

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are ± 5%.

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are  $\pm 5\%$ .