

Tuff-Seal Interlocking Tile Maintenance

Care & Maintenance

Tuff Seal Interlocking Floor Tile is compatible with most normal maintenance practices. The procedures you choose should be based on the size of the area installed, the gloss level you prefer (high or low gloss), the type maintenance equipment you plan to use.

Initial cleanup and maintenance

1. Remove all surface soil, debris, sand and grit by sweeping, dust mopping or vacuuming
2. Scrub the floor with a neutral pH (7-8.5) detergent
 - Apply cleaning solution with a mop/bucket, scrub with rotary scrubber with soft nylon brushes or an automatic scrubber with soft nylon brushes
 - Pick up solution with wet-vac or mop/bucket
 - Rinse with clean water, allow to dry

3. Then apply option 3A or 3B

Option 3A: Apply floor finish

- Apply 3-4 thin coats of high quality, commercial, acrylic floor finish with clean finish mop or applicator
- Allow 30 minutes dry time between each coat option

Option 3B: Dry maintenance method

- Spray, clean and buff using a rotary machine (175-1500 rpm) with an appropriate pad and spray buff solution.

Regular maintenance (as often as required)

1. Remove all surface soil, debris, sand and grit by sweeping, dust mopping or vacuuming

Option 1A: Dry maintenance method

- Spray, clean and buff using a rotary machine (175-1500 rpm) with an appropriate pad and spray buff solution.

Option 1B: Wet maintenance method

- Scrub or mop with neutral pH (7-8.5) detergent. If floor is exposed to grease or oil, use a degreasing detergent
- Apply cleaning solution with a mop/bucket, scrub with rotary scrubber with soft nylon brushes or automatic scrubber with soft nylon brushes
- Pick up solution with a wet vac or mop/bucket
- Rinse with clean water, allow to dry

Tuff-Seal Interlocking Tile Maintenance continued

Periodic scrub and recoat

1. Remove all surface soil, debris, sand and grit by sweeping, dust mopping or vacuuming

- Heavy scrub using rotary scrubber or automatic scrubber with scrubbing pad and double-strength neutral pH (7-8.5) detergent
- Pick up solution with a wet vac or mop/bucket
- Rinse with clean water, allow to dry

2. Apply floor finish (optional)

- Apply 1-2 thin coats of high quality, commercial, acrylic floor finish with clean finish mop or applicator
- Allow 30 minutes dry time between each coat

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
877-822-6622
info@greatmats.com
revised 6/2016