

Rubber Tile Interlocking 2x2 Ft Flooring
Material Safety Data Sheet

SECTION 1- MANUFACTURER IDENTIFICATION

MANUFACTURER NAME: U.S.RUBBER RECYCLING INC.
ADDRESS: 1231 Lincoln Street, Colton, CA 92324
EMERGENCY PHONE: 909-825-1200
INFORMATION PHONE: 888-473-8453
PRODUCT NAME: SURVIVOR™ Sportfloor Rolls/Tiles
DATE: 1/26/2013

SECTION 2- HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS#	TLV(ACGIH)	OSHA PEL	WEIGHT%
METHYLENE BIS (PHENYLISOCYANATE)	101-68-8	.005 PPM	.002 PPM	<1.2
DIPHENYLMETHANE DIISOCYANATE	6447-405	.005 PPM	.002 PPM	<.9
POLYMETHYLENE POLYPHENYL ISOCANATE	9016-87-9	.005 PPM	.002 PPM	<.9
AROMATIC HYDROCARBONS	64742-110-6	5.000 PPM	5.000 PPM	

SECTION 3-PHYSICAL DATA

COMPOSITION: Recycled SBR rubber granules bonded with alaphatic isocyanate polymer binding agent
APPEARANCE: solid rubber compound
VISCOSITY: n/a
BOILING POINT: n/a
VAPOR PRESSURE: n/a
PERCENT VOIATILE: n/a
ODOR: Characteristic of tire rubber
MELTING POINT: n/a

SECTION 4- FIRE & EXPLOSION HAZARD DATA

FLASH POINT: N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: CO2, DRY CHEMICALS, FOAM
SPECIAL FIREFIGHTING PROCEDURES: Wear positive pressure self-contained breathing equipment. If water is used, it should be used in large quantities.

SECTION 5- REACTIVITY DATA

STABILITY: STABLE
INCOMPATABILITY: n/a
HAZARDOUS DECOMPOSITION: Carbon monoxide (CO), Carbon dioxide (CO2), Nitrogen oxide.
HAZARDOUS POLYMERIZATION: May occur with incompatible reactants, strong bases, water and high temperature.
CONDITION TO AVOID: Temperatures above 212 degrees F, open flame.

Rubber Tile Interlocking 2x2 Ft Flooring

Material Safety Data Sheet continued

SECTION 6- WASTE DISPOSAL METHOD

Dispose of waste materials in landfill in accordance with all federal, state and local regulations.

SECTION 7- PROTECTION INFORMATION

PROTECTIVE GLOVES: Use natural rubber or Neoprene gloves.

REGULATORY INFORMATION

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME: METHYLENE BIS (PHENYL ISOCYANATE)
CAS# 101---68---8
CONCENTRATION:<1.2

- A) AN IMMEDIATE HEALTH HAZARD
- B) A DELAYED HEALTH HAZARD
- C) A REACTIVE HAZARD

ADDITIONAL HEALTH EFFECTS ASSOCIATED WITH DIPHENYLMETHANE DIISOCYANATE (ALSO MDI: METHYLDIPHENYL DIISOCYANATE)

THE INTERNATIONAL ISOCYANATE INSTITUTE HAS RECENTLY SUBMITTED A PRELIMINARY REPORT OF A LONG TERM INHALATION STUDY CONDUCTED ON POLYMERIC DIPHENYLMETHANE DIISOCYANATE (MDI). IN THIS STUDY, RATS WERE TO RESPIRABLE EXPOSED AEROSOL PARTICLES OF POLYMERIC MDI FOR 6 HOURS/DAY, 5 DAYS/WEEK, FOR 2 YEARS. THE CONCENTRATIONS USED WERE: 0 mg/m³ (CONTROL); 0.2 mg/m³ (LOW) 1.0 mg/m³ (MEDIUM); AND 6mg/m³ (HIGH). HIGH AND MEDIUM EXPOSURES SHOWED CHRONIC IRRITATION AND ACCUMULATION OF YELLOW FLUID THAT ACCOMPANIES LUNG IRRITATION AT THE MEDIUM AND HIGH LEVELS. OUR SUPPLIERS NOTE THAT THE TUMOR EFFECTS NOTED IN THIS STUDY WERE INDUCED AT LEVELS THAT WOULD NOT BE TOLERABLE IN THE WORKPLACE DUE TO THE IRRITANT AND SENSITIZING ANY PROLONGED EXPOSURE LEADING TO CHRONIC IRRITATION AND LUNG DAMAGE, THE TUMOR FORMATION WOULD BE UNLIKELY. AT THIS TIME, MDI HAS NOT BEEN LISTED AS CARINOGENIC NY, NTP, IARC OR OSHA.

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, EXPRESSES OR IMPLIED, EXCEPT THAT IT IS ACCURATE TO THE BEST KNOWLEDGE OF U.S. RUBBER RECYCLING INC. THE DATA ON THESE SHEETS RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN. U.S. RUBBER RECYCLING INC. ASSUMES NO LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON THIS DATA.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
V: 877-822-6622
F: 715-825-4928
info@greatmats.com