



EagleGrip Pacific Urethane Rubber Flooring Adhesive Product Specifications

PRODUCT CHARACTERISTICS	Product Classification	Modified urethane (isocyanate free)
	Base Chemistry Proprietary	STPE polymer-based (Hybrid Propel®)
	Curing Method	Moisture cure
	Appearance	Off white
	Consistency	Smooth, medium viscosity liquid
	Application	Easy troweling
	Flammability	Non-flammable
	Freeze/Thaw	Stable to 10°F (-12°C)
	Shelf Life	1 year
MOISTURE	Moisture Control	Protects flooring against unlimited moisture
	RH	No testing required
	pH	No testing required (5-14)
	MVER	No testing required
TIME	Open Time	0 min
	Flash Time	N/A
	Working Time	45 min
	Cure Time	12 hours
	Pot Life	N/A
TRAFFIC	Light Traffic	6 hrs.
	Heavy Traffic	6 hrs.
	Heavy Rolling Loads	N/A
SUSTAINABILITY	Solvents	None
	Isocyanates	None
	VOC (g/L) - SCAQMD Rule#1168	0.1
	LEED Points	Contributes to low emitting materials
	Certifications	Greenguard, Floor Score

*IIC and STC ranges are flooring assembly specific based on third party testing and verification in a controlled environment.

EagleGrip Pacific Urethane Rubber Flooring Adhesive

Product Specifications – continued

APPROVED FLOORING TYPES

- Pacific Rolled Rubber and Tiles
- Pacific Rubber Underlayment
- Engineered and Solid Hardwood Flooring

APPROVED SUBSTRATES & SURFACES

- APA underlayment grade plywood and OSB
- Association grade particleboard
- Cement backer board
- Cementitious and anhydrite screeds
- Concrete and radiant heated subfloors that do not exceed 85°F (30°C)
- Existing well-bonded non-cushion-backed vinyl, tile, and sheet flooring
- Fully secured cork underlayment's
- Gypsum and lightweight concrete (must be primed with an approved primer)
- Terrazzo (properly prepared with all waxes and surface finishes removed)
- Well-bonded residue from cutback adhesives

SUBSTRATE TESTING

RH - No testing required [ASTM F2170]

pH - No testing required (5-14)

MVER - No testing required [ASTM F1869]

STORAGE

This product should be stored at temperatures between 50-90°F (15-32° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

CLEANING INSTRUCTIONS

While product is still wet: use a damp cloth and water to remove.

While product is still soft: use an approved adhesive remover/stripper, denatured alcohol, or mineral spirits.

Always check compatibility on a piece of scrap flooring.

Greatmats.com
117 Industrial Ave
Milltown W I 54858
Toll free: 877-822-6622
Direct voice: 715-653-6100
info@greatmats.com
Revised 2/2024