



## Rolled Rubber Pacific Product Specifications

Roll Size:	48 inches wide
Thickness:	Available in 1/8, 1/4, 3/8, 1/2 inch, 8 mm
Weight:	1/8 inch – .8 lbs. per sq/ft. 1/4 inch – 1.6 lbs. per sq/ft. 3/8 inch – 2.2 lbs. per sq/ft. 1/2 inch – 2.6 lbs. per sq/ft. 8 mm – 1.9 lbs. per sq/ft.
Material Density:	Shore A 65 +/- 5
Colors:	Available in Black or 10% color fleck
Material:	Recycled rubber
Surfaces Install:	Flat hard surface, indoors
Shipping:	9 rolls per 42x42 inch pallet
Warranty:	5 Year limited manufacturer's

### PRODUCT STANDARDS

ITEM	STANDARD	RATING
Density	D3676	68.3lbs/cubic foot
Tensile Strength	ASTM D412	265 psi
Tear Resistance	ASTM D413	Average Elongation at break 1.52
Hardness	D2240	Shore A 65 +/- 5
Slip Resistance	D C1028	Friction Coefficient .084-.090
Abrasion	D4060	2,000 cycles taber abraser 1kg, 0.329g - 0.35g loss
Flammability	ASTM E648	Critical Radiant Flux <0.10W/cm2
Chemicals	N/A	Resistant to most acids and chlorine
Volatile Organic Compounds	CDPH v1.2	<.05mg/m3

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622

Direct voice: 715-653-6100  
Fax: 715-825-4928  
info@greatmats.com  
Revised 10/2024