



Rubber Tile Interlocking 2x2 Ft Pacific

Product Specifications

Tile Size:	24 x 24 inch
Thickness:	Available in 1/4, 3/8, 1/2 inch, 8 mm
Tile Weight:	1/4 inch – 6 lbs. 3/8 inch – 10 lbs. 1/2 inch – 12 lbs. 8 mm – 7.5 lbs.
Material Density:	Shore A 65 +/- 5
Colors:	Available in Black or 10% color fleck
Material:	Recycled rubber
Surfaces Install:	Flat hard surface, indoors
Shipping:	100 tiles per 42x42 inch pallet
Warranty:	5 Year limited manufacturer's

PRODUCT STANDARDS

ITEM	STANDARD	RATING
Density	D3676	68.3lbs/cubic foot
Tensile Strength	ASTM D412	265 psi
Tear Resistance	ASTM D413	Average Elongation at break 1.52
Hardness	D2240	Shore A 65 +/- 5
Slip Resistance	D C1028	Friction Coefficient .084-.090
Abrasion	D4060	2,000 cycles taber abraser 1kg, 0.329g - 0.35g loss
Flammability	ASTM E648	Critical Radiant Flux <0.10W/cm2
Chemicals	N/A	Resistant to most acids and chlorine
Volatile Organic Compounds	CDPH v1.2	<.05mg/m3

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622

Direct voice: 715-653-6100
Fax: 715-825-4928
info@greatmats.com
Revised 10/2024