

# GREATMATS

## SP-STADIUM SERIES 19

### PRODUCT SUMMARY

Safety Padding Ink Pro Stadium Series is an outdoor wall padding panel. Designed for multiple attachment methods to pre-set T-Nuts. This style panel is an exterior grade wood backed pad with 3" Impact rated polyurethane foam laminated to the face using a two part adhesion process. This combination of foam and wood is wrapped front and sides and securely stapled with galvanized steel staples onto back with exterior rated PVC Vinyl. Total thickness 3 23/32"

### Components

1. Backing - 23/32" Georgia Pacific DryMax® oriented strand board Third-party certified to the Sustainable Forestry Initiative® procurement standard. Engineered to stay flat. Moisture resistance throughout the panel, not just on the surface. Contains no added urea formaldehyde resins. Georgia-Pacific building products can contribute to LEED® certification points.
2. Foam Layer - 3" polyurethane foam meets standards for ASTM 2440. The test method quantifies impact in terms of g-max and Head Injury Criterion (HIC) scores. Compliant with California Fire Safety Law TB 117.
3. Covering - 19 oz. waterproof coated vinyl smooth matte surface. BACshield: highly resistant to mildew and fungus, including UV additives for exceptional resistance to UV rays. Passes CSFM FR test, ASTM E84 (Class A) & NFPA-701 FR tests

### STANDARD MANUFACTURING

Typical panel to be manufactured at 48" width x \_ \_" height as specified All

exposed wood to be additionally seal coated with tinted Exterior Wood Primer All

columns and corners to be pre-fabricated to fit field condition

### COLOR(S)

As selected from available color selector

### INSTALLATION

To be determined by site conditions. Set T-Nut to optional, Z-Clip, Fender Washer, or Pipe Clamp typical. Typical height per current ASTM Standard not more than 4" above finished surface.