



## Wearwell 24/Seven CFR Solid Gritshield 3x3 Ft Mat

Product Specifications

SKU: 574.58x3x3CFRBK

<b>Mat Size:</b>	3x3 ft x 5/8 inch
<b>Weight:</b>	28 lbs.
<b>Color:</b>	Black
<b>Texture:</b>	Solid Gritshield top surface design
<b>Material:</b>	Rubber
<b>Surfaces Install:</b>	Interlocking, dry lay on flat hard surface
<b>Shipping:</b>	8x8x38 inch carton, 50 cartons per standard 4x4 ft pallet

<b>Parameters of Category: Specifications – General</b>	
Suitable Environment	Wet, Oily, Slippery
Type	Anti-Fatigue Flooring
Solid / Drainage	Solid
Compound	Cutting Fluid Resistant Rubber
Recycled	>50%
Warranty	1 year

<b>Test Specification &amp; Results</b>	
<b>Property</b>	<b>Test / Results</b>
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.10 / Wet: COF= 1.10
Compression Deflection	ASTM D 575 / Deflection @35 psi, mm=8.02, inches -.315
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available